

**MATERIAL SAFETY DATA SHEET – RESIN ABC AND PITFILL**  
**VALID UNTIL April 2, 2019**

<p><b>Product Identification</b></p> <ul style="list-style-type: none"> <li>• Trade Name:</li> <li>• Chemical Name:</li> </ul>	<p>RESIN ABC AND PITFILL            Modified Aliphataic Acrulated Urethan            CAS# 79 -10 - 7</p>
<p><b>Physical Data</b></p> <ul style="list-style-type: none"> <li>• Appearance &amp; Odor:</li> <li>• Solubility in water:</li> <li>• Boiling point:</li> <li>• Specific gravity:</li> </ul>	<p>Clear liquid, very slight odor            Nil            100 Degrees Centigrade            &lt; 1</p>
<p><b>Fire Protection</b></p> <ul style="list-style-type: none"> <li>• Flash Point:</li> <li>• Extinguishing Media:</li> </ul>	<p>Over 200 Degrees Centigrade            Carbon Dioxide, dry chemicals, foam</p>
<p><b>Health Hazard Data</b></p> <ul style="list-style-type: none"> <li>• Threshold limit value:</li> <li>• Effects of overexposure:</li> <li>• First Aid &amp; Emergency:</li> </ul>	<p>Not established            May cause skin irritation, contact with eyes causes irritation.            For eyes- flush with water            For skin- wash with soap and water            Inhalation- remove to fresh air            Ingestion- obtain medical attention</p>
<p><b>Reactivity Data</b></p> <ul style="list-style-type: none"> <li>• Stability:</li> <li>• Materials to avoid:</li> <li>• Hazardous Polymerization:</li> </ul>	<p>Stable            Oxidizing agents, excessive heat            Will not occur</p>
<p><b>Spill or Leak Procedure</b></p>	<p>Absorb with inert materials and dispose. Flush area with water.</p>
<p><b>Special protection information</b></p> <ul style="list-style-type: none"> <li>• Ventilation:</li> <li>• Protection:</li> </ul>	<p>Positive fresh air exhaust            Use protective gloves &amp; safety eye glasses. Do not wear contact lenses.</p>

**MATERIAL SAFETY DATA SHEET – ULTRA THIN**  
**VALID UNTIL April 2, 2019**

<b>Product Identification</b> <ul style="list-style-type: none"> <li>• Trade Name:</li> <li>• Chemical Name:</li> </ul>	ULTRA THIN Modified Acrylic Ester
<b>Hazardous Ingredients</b> <ul style="list-style-type: none"> <li>• % by weight</li> <li>• Max. Exposure (8 hr time-wtd avg.)</li> <li>• Cas#</li> </ul>	<1 10 ppm ACGIH TLV 79-10-7
<b>Physical Data</b> <ul style="list-style-type: none"> <li>• Appearance &amp; Odor:</li> <li>• Solubility in water:</li> <li>• Boiling point:</li> <li>• Specific gravity:</li> </ul>	Clear liquid, mild odor Miscible 450 Degrees F @ 9mm/Hg 1.07
<b>Fire Protection</b> <ul style="list-style-type: none"> <li>• Flash Point:</li> <li>• Extinguishing Media:</li> </ul>	Over 200 Degrees F (TCC) Carbon Dioxide, dry chemicals, foam
<b>Health Hazard Data</b> <ul style="list-style-type: none"> <li>• Threshold limit value:</li> <li>• Effects of overexposure:</li> <li>• First Aid &amp; Emergency:</li> </ul>	Not established May cause skin irritation, contact with eyes may cause irritation. For eyes- flush with water For skin- wash with soap and water Inhalation- remove to fresh air Ingestion- low toxicity, obtain medical attention
<b>Reactivity Data</b> <ul style="list-style-type: none"> <li>• Stability:</li> <li>• Materials to avoid:</li> <li>• Hazardous Polymerization:</li> </ul>	Stable Oxidizing agents, excessive heat Will not occur
<b>Spill or Leak Procedure</b>	Flush with chlorinated solvents, recommended due to non-flammibility. Remove with solid waste disposal method.
<b>Special protection information</b> <ul style="list-style-type: none"> <li>• Ventilation:</li> <li>• Protection:</li> </ul>	Positive fresh air exhaust Use protective gloves & safety eye glasses. Do not wear contact lenses.